620979

#### CENTRAL INTELLIGENCE AGENCY

## INFORMATION REPORT

This Document contains information affecting the National Defense of the United States, within the meaning of Title 18, Sections 793 and 794, of the U.S. Code, as amended. Its transmission or revelation of its contents to or receipt by an unauthorized person is prohibited by law. The reproduction of this form is prohibited.

	SECRET/CONTROL - U.S. OF	FICIALS ONLY		
COUNTRY	Austria	REPORT	25X1	
SUBJECT	Production of the SMV Schwechat and Lobau Refineries	DATE DISTR.	6 July 19 4	- 954
DATE OF INFO.		REQUIREMENT NO.	RD	25X1 25X1
	This is UNEVALUA	ATED Information	A Section 4	
	THE SOURCE EVALUATIONS IN THIS RE THE APPRAISAL OF CONTENT I (FOR KEY SEE REVERS	IS TENTATIVE.		
				25 <b>X</b> 1
SCI	HWECHAT REFINERY (March 1954)			
1.				
	No. 1. Amount of crude oil processe		klaa)	
	Gasoline 17.0 %		•	
	Kerosene 28,2 %	6		
	Gasoil 23.6 9	6		
	Residue 30.09	1		

This installation was not in use for 12 days of the month.

1.2 %

No. 2. Amount of crude oil processed: 11,040 tons (Matzen)

 Gasoline
 4.1 %

 Kerosene
 9.8 %

 Gasoil
 26.2 %

 Residue
 58.7 %

 Loss
 1.2 %

Loss

This installation was not in use for 7 days of the month.

## 25 YEAR RE-REVIEW

#### SECRET/CONTROL - U.S. OFFICIALS ONLY

									·		 			<del></del>
STATE	х	ARMY	x	NAVY	x	AIR '	x	FB1		AEC			1	

(Note: Washington Die Sution Indicated By "X"; Field Distribution By "#".)

SECRET/CONTROL - U.S. OFFICIALS ONLY
- 2 -

# Cracking Installation (Atmospheric Plant)

#### First Processing

Amount of crude oil (Matzen) 12,690 tons.

Gasoline

4.4 %

Kerosene

11.8%

Gasoil

22.4 %

Residue

60.1 %

Loss

1.3 %

This installation was not in use for 4 days of the month.

### Cracking Process

Amount of crude oil processed: 19,118 tons (Matzen-Masut)

Light and Heavy Gasoline - 30.2 %

Cracked Benzin (Spaltgas) - 8.7 %

Residue

- 59.3 %

Loss

- 1.8%

Note: The converted vacuum installation was not in operation during the month of March.

## 2. Deliveries.

The following percentage deliveries were made during the month of March:

Gasoline:

100% to the central storage depot at Lobau.

Kerosene:

55% to the central storage depot at Lobau.

Topade and a solution and popular.

25X1

Gasoil:

100% to the central storage depot at Lobau.

Furnace oil: 40% to the central storage depot at Lobau.

25X1

25% to Czechoslovakia.

Bitumen:

80% to local Austrian industry.

20% as soft bitumen to Poland.

SECRET/CONTROL - U.S. OFFICIALS ONLY

煙

SECRET/CONTROL - U.S. OFFICIALS ONLY
- 3 -

# LOBAU REFINERY ( March 1954)

## 3. Atmospheric Installations - Production.

No. 1. Amount of crude oil processed: 21,995 tons (Aderklaa)
Gasoline 22.3 %

Kerosene 26.1 %

Gasoil 18.8%

Residue 31.6 %

Loss 1.2 %

This installation was not in use for 6 days of the month.

# No. 2. Amount of crude oil processed: 11,760 tons (Matzen)

Gasoline 4.2 %

Kerosene 9.5 %

Gasoil 25.8 %

Residue 59.3 %

Loss 1.2 %

4. <u>Deliveries</u>.

Gasoline - 100 % pumped to the central storage depot at Lobau.

Kerosene - 70 % to the central storage depot at Lobau.

30 % to Czechoslovakia.

Gasoil - 40% to the central storage depot at Lobau.

25X1

Furnace-oil-60% to the central storage depot at Lobau.

25% to local Austrian industry.

25X1

5. a. The difference in the yield obtained from Matzen and Aderklaa crude oils lies in the composition of these oils. When top-processed, Matzen crude oil produces approximately 6% gasoline at a temperature of 300-350°C. If the top residue is then

SECRET/CONTROL - U.S. OFFICIALS ONLY

SECRET/CONTROL - U.S. OFFICIALS ONLY

25X1

- 4 -

cracked a further 30%, gasoline is produced at a temperature of 450 to 500°C. The Aderklaa crude oil is also top-processed and produces up to 28% gasoline at a temperature of approximately 350°C. The crude oil has however different properties and is a paraffin-oil.

b. The difference in the production lies in the method of running the installation and is governed by the management dependent upon whether a light or a heavy distillation is to be produced.

SECRET/CONTROL - U.S. OFFICIALS ONLY